

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the above-identified application:

1. (previously presented) A fault detection system for detecting faults in a turbine engine, the fault detection system comprising:

a sensor data processor, the sensor data processor configured to receive sensor data from the turbine engine and augment the sensor data to provide an augmented data set, wherein the sensor data processor is configured to augment the sensor data by generating residuals from the sensor data and determining a rate of change of the residuals; and

a fuzzy logic inference system, the fuzzy logic inference system configured to receive the augmented data set, and wherein the fuzzy logic inference system includes a plurality of membership functions and wherein each of the plurality of membership functions is associated with at least one data type in the augmented data set, and wherein the fuzzy logic system is configured to fuzzify the augmented data set using the plurality of membership functions and analyze the augmented data set to determine a likelihood that a fault has occurred in the turbine engine.

2. (withdrawn) The system of claim 1 wherein the sensor data processor is configured to augment the sensor data by determining a rate of change of the sensor data.
3. (cancelled).

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

4. (cancelled)
5. (previously presented) The system of claim 1 wherein the sensor data processor is configured to augment the sensor data by computing a margin for the sensor data.
6. (previously presented) The system of claim 1 wherein the sensor data comprises engine speed data, fuel flow data and exhaust gas temperature data.
7. (previously presented) The system of claim 1 wherein the sensor data processor is configured to receive exhaust gas temperature data and wherein the sensor data processor is configured to augment the exhaust gas temperature data by determining exhaust gas temperature margin data corresponding to a difference between the exhaust gas temperature data and a maximum safe temperature.
8. (cancelled)
9. (previously presented) The system of claim 1 wherein the fuzzy logic inference system includes a plurality of rules, and wherein the fuzzy logic system is configured to evaluate the fuzzified augmented data set according to the plurality of rules.

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

10. (previously presented) The system of claim 9 wherein the fuzzy logic inference system is further configured to aggregate outputs of the plurality of rules and defuzzify the aggregated output for input into a diagnostic system.

11. (currently amended) The system of claim 10 wherein the aircraft system comprises a turbine engine and wherein the sensor data comprises exhaust gas temperature data, engine speed data, and fuel flow data, and wherein the sensor data processor is configured to augment the sensor data by generating residuals from the exhaust gas temperature data, engine speed data, and fuel flow data, and wherein the sensor data processor is configured to further augment the sensor data by determining a rate of change of the residuals, and wherein the sensor data processor is configured to further augment the sensor data by determining a margin for the exhaust gas temperature data corresponding to a difference between the exhaust gas temperature data and a selected maximum safe exhaust gas temperature for the turbine engine.

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

12. (cancelled)

13. (cancelled)

14. (cancelled)

15. (cancelled)

16. (cancelled)

17. (cancelled)

18. (cancelled).

19. (cancelled).

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

20. (cancelled)

21. (withdrawn) A program product comprising:

a) a fault detection program, the fault detection program including:

a sensor data processor, the sensor data processor configured to receive sensor data from a turbine engine and augment the sensor data to provide augmented data set, wherein the sensor data processor is configured to augment the sensor data by generating residuals from the sensor data and determining a rate of change of the residuals; and

a fuzzy logic inference system, the fuzzy logic inference system configured to receive the augmented data set, and wherein the fuzzy logic inference system includes a plurality of membership functions and wherein each of the plurality of membership functions is associated with at least one data type in the augmented data set, and wherein the fuzzy logic system is configured to fuzzify the augmented data set using the plurality of membership functions and analyze the augmented data set to determine a likelihood that a fault has occurred in the turbine engine; and

b) computer-readable media bearing said fault detection program.

22. (cancelled)

23. (cancelled)

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

24. (cancelled)

25. (withdrawn) The program product of claim 21 wherein the sensor data comprises engine speed data, fuel flow data and exhaust gas temperature data

26. (withdrawn-currently amended) The program product of claim 21 wherein the sensor data processor is configured to receive exhaust gas temperature data and wherein the sensor data processor is configured to augment the exhaust gas temperature data by determining exhaust gas temperature margin data corresponding to a difference between the exhaust gas temperature data and a selected maximum safe exhaust gas temperature for the turbine engine.

27. (cancelled)

28. (withdrawn) The program product of claim 21 wherein the fuzzy logic inference system includes a plurality of rules, and wherein the fuzzy logic system is configured to evaluate the fuzzified augmented data set according to the plurality of rules.

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

29. (withdrawn) The program product of claim 28 wherein the fuzzy logic inference system is further configured to aggregate outputs of the plurality of rules and defuzzify the aggregated output for input into a diagnostic system.
30. (withdrawn-currently amended) The program product of claim 21 wherein the sensor data comprises exhaust gas temperature data, engine speed data, and fuel flow data, and wherein the sensor data processor is configured to augment the sensor data by generating residuals from the exhaust gas temperature data, engine speed data, and fuel flow data, and wherein the sensor data processor is configured to further augment the sensor data by determining a rate of change of the residuals, and wherein the sensor data processor is configured to further augment the sensor data by determining a margin for the exhaust gas temperature data corresponding to a difference between the exhaust gas temperature data and a selected maximum safe exhaust gas temperature for the turbine engine.

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

31. (currently amended) An apparatus comprising:

- a) a ~~computing~~ processor;
- b) a memory coupled to the processor;
- c) a fault detection program residing in memory and being executed by the ~~computing~~ processor, the fault detection program including:
 - i) a sensor data processing program ~~processor~~, the sensor data processing program ~~processor~~ configured to receive sensor data from a turbine engine and augment the sensor data to provide augmented data set, wherein the sensor data processing program ~~processor~~ is configured to augment the sensor data by generating residuals from the sensor data and determining a rate of change of the residuals; and
 - ii) a fuzzy logic inference program ~~system~~, the fuzzy logic inference program ~~system~~ configured to receive the augmented data set, and wherein the fuzzy logic inference program ~~system~~ includes a plurality of membership functions and wherein each of the plurality of membership functions is associated with at least one data type in the augmented data set, and wherein the fuzzy logic program ~~system~~ is configured to fuzzify the augmented data set using the plurality of membership functions and analyze the augmented data set to determine a likelihood that a fault has occurred.

32. (cancelled)

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

33. (original) The apparatus of claim 31 wherein the sensor data comprises engine speed data, fuel flow data and exhaust gas temperature data.
34. (currently amended) The apparatus of claim 31 wherein the sensor data processing program system is configured to receive exhaust gas temperature data and wherein the sensor data processor is configured to augment the exhaust gas temperature data by determining exhaust gas temperature margin data corresponding to a difference between the exhaust gas temperature data and a selected maximum safe exhaust gas temperature for the turbine engine.
35. (cancelled)
36. (currently amended) The apparatus of claim 31 wherein the fuzzy logic inference program system includes a plurality of rules, and wherein the fuzzy logic system is configured to evaluate the fuzzified augmented data set according to the plurality of rules.
37. (currently amended) The apparatus of claim 36 wherein the fuzzy logic inference program system is further configured to aggregate outputs of the plurality of rules and defuzzify the aggregated output for input into a diagnostic system.

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

38. (currently amended) The apparatus of claim 31 wherein the sensor data comprises exhaust gas temperature data, engine speed data, and fuel flow data, and wherein the sensor data processing program ~~system~~ is configured to augment the sensor data by generating residuals from the exhaust gas temperature data, engine speed data, and fuel flow data, and wherein the sensor data processing program ~~system~~ is configured to further augment the sensor data by determining a rate of change of the residuals, and wherein the sensor data processing program ~~system~~ is configured to further augment the sensor data by determining a margin for the exhaust gas temperature data corresponding to a difference between the exhaust gas temperature data and a ~~selected~~ maximum safe exhaust gas temperature for the turbine engine.

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

39. (new) A fault detection system for detecting faults in a turbine engine, the fault detection system comprising:

a sensor data processor, the sensor data processor configured to:

receive sensor data from the turbine engine, the sensor data including exhaust gas temperature data, engine speed data, and fuel flow data;

generate exhaust gas temperature residuals by comparing the exhaust gas temperature data to expected values of exhaust gas temperature;

generate engine speed residuals by comparing the engine speed data to expected values of engine speed;

generate fuel flow residuals by comparing the fuel flow data to expected values of fuel flow;

determine a rate of change of the exhaust gas temperature residuals;

determine a rate of change of the engine speed residuals;

determine a rate of change of the fuel flow residuals; and

a fuzzy logic inference system, the fuzzy logic inference system configured to receive the exhaust gas temperature residuals, the engine speed residuals, the fuel flow residuals, the rate of change of the exhaust gas temperature residuals, the rate of change of the engine speed residuals, and the rate of change of the fuel flow residuals, and wherein the fuzzy logic inference system includes a plurality of membership functions, and wherein the fuzzy logic system is configured to fuzzify the exhaust gas temperature residuals, the engine speed residuals, the fuel flow residuals, the rate of change of the exhaust gas temperature residuals, the rate of change of the engine speed residuals, and the rate of change of the fuel flow residuals using the plurality of membership functions to determine a likelihood that a fault has occurred in the turbine engine.

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

40. (new) The system of claim 39 wherein the plurality of membership functions include a low membership function, a medium membership function, and a high membership function.
41. (new) The system of claim 40 wherein the low membership function comprises a first sigmoid function, and wherein the medium membership function comprises a trapezoid function, and wherein the high membership function comprises a second sigmoid function.
42. (new) The system of claim 40 wherein the fuzzy logic inference system is configured to fuzzify the exhaust gas temperature residuals, the engine speed residuals, the fuel flow residuals, the rate of change of the exhaust gas temperature residuals, the rate of change of the engine speed residuals, and the rate of change of the fuel flow residuals using the plurality of membership functions by generating an aggregated output function from the plurality of membership functions.
43. (new) The system of claim 42 wherein the fuzzy logic inference system is configured to determine a likelihood that a fault has occurred in the turbine engine by determining a centroid of area under the aggregated output function.
44. (new) The system of claim 43 wherein the fault comprises a high pressure spool fault.

Appl. No. 10/628,085
Amdt. Dated September 4th, 2007
Reply to Office Action of June 1, 2007

45. (new) The system of claim 39 wherein the sensor data processor is configured to determine the rate of change of the exhaust gas temperature residuals using a linear fit of the exhaust gas temperature residuals, and wherein the sensor data processor is configured to determine the rate of change of the engine speed residuals using a linear fit of the engine speed residuals, and wherein the sensor data processor is configured to determine the rate of change of the fuel flow residuals using a linear fit of the fuel flow residuals.